

## REDUCING ADAPTORS



PROSPOT NO	REDUCING ADAPTORS	MALE	DIA	FEMALE	DIA	L
A16-A13	5/8" 5 Deg Male To 1/2" 5 Deg Female	16	5 Deg	12.7	5 Deg	45
AMT16-A13	5/8" MT Male To 1/2" 5 Deg Female	16	No2 MT	12.7	5 Deg	45
A19-A13	3/4" 5 Deg Male To 1/2" 5 Deg Female	19	5 Deg	12.7	5 Deg	45
A19-A16	3/4" 5 Deg Male To 5/8" 5 Deg Female	19	5 Deg	16	5 Deg	70

## DOUBLE BEND CAP ADAPTORS



PROSPOT NO	ADAPTORS BS 807 5 DEG TO ISO 1:10 TAPER	CAP	DIA	TAPER DIA	DIA	HOLE DIA	CAP DIA	TAPER LENGTH	O/A LENGTH	OFF SET	HOLE DIA
DBA 13	1/2" Adaptor To Suit 13mm Caps	13mm	13	12.7	5 Deg	7	10	18	70	19	6.5
DBA16-125-13	5/8" Adaptor To Suit 13mm Caps	13mm	16	16	5 Deg	7	10	25	80	12.5	6.5
DBA16-32-13	5/8" Adaptor To Suit 13mm Caps	13mm	16	16	5 Deg	7	10	25	90	32	6.5
DBA16-125-16	5/8" Adaptor To Suit 16mm Caps	16mm	16	16	5 Deg	8	12	25	80	12.5	8
DBA16-32-16	5/8" Adaptor To Suit 16mm Caps	16mm	16	16	5 Deg	8	12	25	90	32	8
DBA16-125-20	5/8" Adaptor To Suit 20mm Caps	20mm	16	16	5 Deg	8	15	25	80	12.5	9
DBA16-16MT	5/8" Adaptor To Suit 16mm Caps	16mm	16	16	No2 MT	8	12	25	90	32	8
DBA 0	3/4" Adaptor To Suit 13mm Caps	13mm	19	19	5 Deg	9	10	30	110	32	6.5
DBA 1	3/4" Adaptor To Suit 16mm Caps	16mm	19	19	5 Deg	9	12	30	110	32	8
DBA 2	3/4" Adaptor To Suit 20mm Caps	20mm	19	19	5 Deg	9	15	30	110	32	9
DBA 3	3/4" Adaptor To Suit 16mm Caps	16mm	19	19	5 Deg	9	12	30	85	14	8

Adaptors with different tapers ie, 1:10 & 1:20 are also available. Please ask for details.

## THREADED ADAPTORS



Threaded adaptors are available in numerous configurations with any thread and taper combinations.